

8 x Nics**Console****1U**

Specifications:

Processor	CPU	Intel® Pentium®/ Gen 2-3 th Core™ i3/i5/i7
	Chipset	SOC
	BIOS	AMI
Memory	Type	DDR3/DDR3L
	Socket	SO-DIMM
	Channel	1
	Max Size	8GB
Graphics	GPU	Refer to ark.intel.com
Network	Controller	Intel 82574L/I-211
	Interface	8 x RJ45
I/O	USB	2 x USB3.0
Storage	Socket 1	1 x mSATA SSD
	Socket 2	1 x 2.5" SATA 6 Gb/s
	Auto Power On	Enabled
Operation System Supported	Router OS	pfSense or any freeBSD based router systems
	Linux/Windows	Support
Power	Power Type	ATX
	Power Supply	50W 12V 4.2A/ 100W 100V-240V 50Hz/60Hz
Mechanical	Dimensions	430 x 300 x 50mm
	Rack Ears	Yes
Environment	Operating Temperature	0°C~70°C Centigrade (32°F~140°F)
	Relative Humidity	10%~90% (non-condensing)
Certification		CE, FCC, Rohs

NFA-RS14 Series

Intel® Pentium®/ Gen 2-3th Core™ i3/i5/i7 Processor-Based 1U
 Network Firewall Appliance

Key Features:

- Intel® Pentium®/ Gen 2-3th Core™ i3/i5/i7 BGA Processor and Intel® SOC Chipset
- Rich I/O: Console, 2 x USB3.0, 8 x LAN, VGA, Power switch, ATX power socket
- Single SODIMM DDR3/DDR3L, up to 8GB Memory
- Rich Storage: mSATA SSD, 2.5 Inch SSD/HDD
- Chassis Form: Standard 1U Cabinet Type

Figure:



Ordering Information:

Model	CPU
RS11-B950	Intel® Pentium® Processor B950
RS11-2328M	Intel® Core™ i3-2328M Processor
RS11- 2350M	Intel® Core™ i3-2350M Processor
RS14-2367M	Intel® Core™ i3-2367M Processor
RS11-3110M	Intel® Core™ i3-3110M Processor
RS11-2520M	Intel® Core™ i5-2520M Processor
RS14-2467M	Intel® Core™ i5-2467M Processor
RS11-3320M	Intel® Core™ i5-3320M Processor
RS11-2620M	Intel® Core™ i7-2620M Processor
RS11-3520M	Intel® Core™ i7-3520M Processor
RS14-3517U	Intel® Core™ i7-3517U Processor